



GL019 LG

1W, 65lm mini low glare ground light

FEATURES

IP rating	IP68
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR<16
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	204g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL019LGFNW	Stainless steel 316	1W	4000K	30°	65	65	262	
GL019LGSNW	Stainless steel 316	1W	4000K	12°	65	65	908	

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



1W at 350mA or 2W at 700mA



Honeycomb baffle for low glare and visual comfort



Low voltage ground light

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Compact yet powerful fitting

Shallow depth for easy installation

Robust cable for outdoor use

Marine-grade stainless steel 316

PATENT: **GB2544975 EP3176502**

