



1W at 350mA or 2W at 700mA



Honeycomb baffle for low glare and visual comfort

Low voltage ground light

GL019 LG

1W, 65lm mini low glare ground light

Features

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
UGR	UGR<16, UGR<19, UGR<22
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	204g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Compact yet powerful fitting
- Shallow depth for easy installation
- Robust cable for outdoor use
- Marine-grade stainless steel 316

Patent Information

GB2544975 EP3176502

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL019LGFNW	Stainless steel 316	1W	4000K	30°	65	65	262	
GL019LGSNW	Stainless steel 316	1W	4000K	12°	65	65	908	
GL019LGFWW	Stainless steel 316	1W	3000K	30°	55	55	222	
GL019LGSWW	Stainless steel 316	1W	3000K	12°	55	55	768	
GL019LGF27	Stainless steel 316	1W	2700K	30°	53	53	214	
GL019LGS27	Stainless steel 316	1W	2700K	12°	53	53	740	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

