



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage ground light

GL019 SQ

Up to 2W, 130lm square mini ground light

Features

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	134g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Square baffle for a different decorative effect
- Shallow depth for easy installation
- Marine-grade stainless steel 316

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	350mA				700mA				Energy
				W	lm	lm/W	Ix @ 1m	W	lm	lm/W	Ix @ 1m	
GL019 SQ F NW	Stainless steel	4000K	20°	1W	90	35	396	2W	130	-	572	
GL019 SQ S NW	Stainless steel	4000K	12°	1W	90	90	1833	2W	130	65	2648	
GL019 SQ F WW	Stainless steel	3000K	20°	1W	80	90	353	2W	125	65	551	
GL019 SQ F BLUE	Stainless steel	Blue	20°	1W	10	90	44	2W	20	65	88	
GL019 SQ S BLUE	Stainless steel	Blue	12°	1W	10	10	204	2W	20	10	407	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

