



collingwood



1W at 350mA or 2W at 700mA



Coastal protected

Low voltage ground light

GL019 SQ

Features

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	50°C
Weight	134g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Square baffle for a different decorative effect
- Shallow depth for easy installation
- Marine-grade stainless steel 316

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL019 SQ F NW	Stainless steel	20°	1W (350mA)	4000K	90	35	396	
			2W (700mA)	4000K	130	-	396	
GL019 SQ S NW	Stainless steel	12°	1W (350mA)	4000K	90	90	1833	
			2W (700mA)	4000K	130	65	1833	
GL019 SQ F WW	Stainless steel	20°	1W (350mA)	3000K	80	90	353	
			2W (700mA)	3000K	125	65	353	
GL019 SQ F BLUE	Stainless steel	20°	1W (350mA)	Blue	10	90	44	
			2W (700mA)	Blue	20	65	44	
GL019 SQ S BLUE	Stainless steel	12°	1W (350mA)	Blue	10	10	204	
			2W (700mA)	Blue	20	10	204	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PLU/700 3-9	220-240V	Yes	No	0	3	9
PSIP70018W	220-240V	Yes	No	0	1	8

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

