



1W at 350mA



Baffled for low glare and visual comfort

Low voltage ground light

GL019 Ultra low-glare

Features

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
UGR	UGR<16, UGR<19, UGR<22
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

Installation Information

Input	350mA
Maximum Ambient Temperature	50°C
Weight	260g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Perfect for both interior and exterior applications
- Compliments environments with ultra low glare up-lighting effect
- Marine-grade stainless steel 316 or Brass

Patent Information

GB2544975 EP3176502

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL019DNBL40	Stainless steel	1W	4000K	12°	78	78	2369	
GL019DMBL30	Stainless steel	1W	3000K	30°	64	64	25	
GL019DNBL30	Stainless steel	1W	3000K	12°	74	74	1324	
GL019DMBL27	Stainless steel	1W	2700K	30°	60	60	24	
GL019DNBL27	Stainless steel	1W	2700K	12°	70	70	1292	
GL019BNBL40	Black	1W (350mA) / 2W (700mA)	4000K	12°	78	78	2369	
GL019ANBL30	Antique brass	1W	3000K	12°	74	74	1272	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

