



1W

1W at 350mA



Baffled for low glare and visual comfort



Low voltage ground light

GL019 ULTRA LOW-GLARE

1W, 78lm mini ground light

FEATURES

IP rating	IP68
IK rating	IK06
CSP Switchable	Single CCT
UGR	UGR<16
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	50°C
Weight	260g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL019DNBL40	Stainless steel	1W (350mA) / 2W (700mA)	4000K	12°	78	78	2369	
GL019DMBL30	Stainless steel	1W (350mA) / 2W (700mA)	3000K	30°	64	64	25	
GL019DNBL30	Stainless steel	1W (350mA) / 2W (700mA)	3000K	12°	74	74	1324	
GL019DMBL27	Stainless steel	1W (350mA) / 2W (700mA)	2700K	30°	60	60	24	
GL019DNBL27	Stainless steel	1W (350mA) / 2W (700mA)	2700K	12°	70	70	1292	
GL019BNBL40	Black	1W (350mA) / 2W (700mA)	4000K	12°	78	78	2369	
GL019ANBL30	Antique brass	1W (350mA) / 2W (700mA)	3000K	12°	74	74	1272	

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
-----------------	----------------------------	-----------------

WARRANTY

Warranty

7 years


FEATURES & BENEFITS

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

Marine-grade stainless steel 316 or Brass

PATENT: **GB2544975 EP3176502**



TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

This ultra low-glare, IP68 ground light is a stunning product for illuminating entrance halls, pathways and circulation areas of both interiors and exteriors. The light source is recessed further back into the ground keeping it hidden from view, but still provides a powerful upwards light beam. This marine-grade stainless steel unit will give a flawless performance for many years of maintenance-free operation. Available in three colour temperatures and two beam angles, this product will suit any interior or exterior design.