



1W at 350mA or 2W at 700mA



Frosted effect for low glare and soft lighting



Low voltage ground light

GL019 FROSTED

1W, 13lm frosted mini ground light

FEATURES

IP rating	IP68
IK rating	IK06
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	50°C
Weight	196g
Inrush Current	N/A
Cut Out Size	33
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Beam	W	Colour	lm	lm/W	lx@1m	Energy
GL019DC0F40	Stainless steel	100°	1W (350mA)	4000K	13	13	5	
GL019DC0F27	Stainless steel	100°	1W (350mA)	2700K	10	10	4	
GL019DC0FBL	Stainless steel	100°	1W (350mA)	Blue	2	2		
GL019BC0F27	Black	100°	1W (350mA)	2700K	10	10	4	
GL019BC0F40	Black	100°	1W (350mA)	4000K	13	13	5	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP70018W	220-240V	Yes	No	0	1	8

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Robust cable for outdoor use

Shallow depth for easy installation

PATENT: **GB2544975 EP3176502**

BEAM ANGLE: **100°**

