



1W at 350mA



Coastal protected

Low voltage groundlight

GL022

Square 30° slotted LED ground / step light

Features

IP rating	IP68
IK rating	IK07
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	400g
Inrush Current	N/A
Cut Out Size	50
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Angled light, ideal for use as a step light
- Robust cable for outdoor use
- Brushed stainless steel for sleek effect

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL022 NW	Stainless steel	1W	4000K	30°	10	10	10	
GL022 WW	Stainless steel	1W	3000K	30°	8	8	8	
GL022 27	Stainless steel	1W	2700K	30°	8	8	7	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/50	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

