



GL034 MAINS

Hooded Mains Ground Light

FEATURES

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
Tilttable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	GL034AB: 1420g, GL034BK: 680g, GL034BZ: TBC, GL034SS: 850g
Inrush Current	GL034SS: 60A 0.037ms, Other Variant: TBC
Cut Out Size	80-85mm
Construction Material	Stainless steel 316
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
GL034SS22MF	Stainless steel 316	2.8W	2200K	40°	154	55	
GL034SS27MF	Stainless steel 316	2.8W	2700K	40°	184	66	
GL034SS30MF	Stainless steel 316	2.8W	3000K	40°	186	66	
GL034SS40MF	Stainless steel 316	2.8W	4000K	40°	192	69	
GL034AB22MF	Antique brass	2.8W	2200K	40°	154	55	
GL034AB27MF	Antique brass	2.8W	2700K	40°	184	66	
GL034AB30MF	Antique brass	2.8W	3000K	40°	186	66	
GL034AB40MF	Antique brass	2.8W	4000K	40°	192	69	
GL034BK22MF	Black	2.8W	2200K	40°	154	55	
GL034BK27MF	Black	2.8W	2700K	40°	184	66	

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

ACCESSORIES

JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick release waterproof joint	Sold Separately

IP65 IP65 perfect for internal or external applications

 Coastal protected

IK08 IK08 impact protection - walk over (Stainless Steel only)

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Supplied complete with installation tube
SDCM3 ensuring uniform light appearance and consistency
Single LED and lens combination for maximum efficiency and optimal light distribution
CRI 80 providing true colour appearance
Available in a new 2200K setting to create a warm and cosy environment with minimal disruption to natural habitat
Long lifetime of 70,000hrs
Available in an array of colours

