



GL034

Hooded LED ground light

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	724g
Inrush Current	60A 0.037ms
Cut Out Size	80-85
Construction Material	Stainless steel 316 (top) / aluminium (body)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL034DWBM27	Stainless steel	2.9W	2700K	40°	170	59	320	
GL034DWBM30	Stainless steel	2.9W	3000K	40°	180	62	338	
GL034DWBM40	Stainless steel	2.9W	4000K	40°	190	66	357	

Wiring Information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

Installation tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick release waterproof joint	Sold Separately



collingwood



2.9W



Coastal protected



Main voltage ground light

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316
- Long lifetime of 70,000hrs
- 7 year warranty

