



GL034

Hooded LED ground light

FEATURES

| | |
|-------------------------------|--------------------------------------------------|
| IP rating | IP65 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Tiltable | No |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over (Stainless Steel & Antique Brass Only) |

INSTALLATION INFORMATION

| | |
|------------------------------------|----------------------------------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 35°C |
| Weight | 724g |
| Inrush Current | 60A 0.037ms |
| Cut Out Size | 80-85 |
| Construction Material | Stainless steel 316 (top) / aluminium (body) |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | Yes |

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|-----------------|------|--------|------|-----|------|---------|--------|
| GL034DWBM30 | Stainless steel | 2.9W | 3000K | 40° | 180 | 62 | 338 | |

WIRING INFORMATION

| | |
|--------------------------------|-----------------------------------------------------|
| Cable / Flying Lead | 1m H05RN-F rubberised cable (outside diameter: 7mm) |
| Type of Wiring Required | Parallel |
| Input Cable Type | H05RN-F (7MM OD) 3 CORE |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes | No | 2 |

ACCESSORIES

| | | |
|--------------------------|---------------------------------|-----------------|
| Installation tube | For easy ground installation | Included |
| JB5 | Gel filled waterproof connector | Sold Separately |
| WC 5-9 | Quick release waterproof joint | Sold Separately |



2.9W



Coastal protected



Main voltage ground light

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Marine grade stainless steel 316

Long lifetime of 70,000hrs

7 year warranty

Ø98mm



83mm

190mm