



2.9W at 350mA or 6W at 700mA



Coastal protected



Mains voltage groundlight

GL038

2.9W, 300lm ground light

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	696g
Inrush Current	60A 0.037ms
Cut Out Size	80-85
Construction Material	Stainless steel 316 (top) / aluminium (body)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316 or antique brass
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL038DWBM27	Stainless steel 316		2.9W	2700K	40°	280	96	526	A+ E
GL038DWBM30	Stainless steel 316		2.9W	3000K	40°	290	100	544	A+ E
GL038DWBM40	Stainless steel 316		2.9W	4000K	40°	300	103	563	A+ D
GL038AWBM27	Antique brass	Antique Brass	3.6W	2700K	40°	280	96	526	A+ E
GL038AWBM30	Antique brass	Antique Brass	3.6W	3000K	40°	290	100	544	A+ E

Wiring Information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

