



2.9W



Coastal protected



Mains voltage groundlight

GL038

2.9W, 300lm ground light

Features

IP rating	IP65
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	696g
Inrush Current	60A 0.037ms
Cut Out Size	80-85
Construction Material	Stainless steel 316 (top) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316 or antique brass
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL038DWBM27	Stainless steel 316		2.9W	2700K	40°	280	96	526	A A B E
GL038DWBM30	Stainless steel 316		2.9W	3000K	40°	290	100	544	A A B E
GL038DWBM40	Stainless steel 316		2.9W	4000K	40°	300	103	563	A A B D E
GL038AWBM27	Antique brass	Antique Brass	2.9W	2700K	40°	280	96	526	A A B E
GL038AWBM30	Antique brass	Antique Brass	2.9W	3000K	40°	290	100	544	A A B E

Wiring Information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

