

2.9W 2.9W

Coastal protected

AC Mains voltage groundlight

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Marine grade stainless steel 316 or antique brass

Long lifetime of 70,000hrs

GL038

2.9W, 300lm ground light

FEATURES

IP rating	IP65
IK rating	IK06
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	0.754
Inrush Current	9A 0.8ms
Cut Out Size	80-85
Construction Material	Brass
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL038DWBM40	Stainless steel 316	Stainless Steel	2.9W	4000K	40°	300	103	563	A+ D
GL038AWBM27	Antique brass	Antique Brass	2.9W	2700K	40°	280	96	526	A+ E
GL038AWBM30	Antique brass	Antique Brass	2.9W	3000K	40°	290	100	544	A+ E

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

ACCESSORIES

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

BEAM ANGLE: 40°

