

**2.9W** 2.9W

**Coastal protected**

**AC** Mains voltage groundlight

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Marine grade stainless steel 316 or antique brass

Long lifetime of 70,000hrs

## GL038

2.9W, 300lm ground light

### FEATURES

IP rating	IP65
IK rating	IK06
CSP Switchable	Single CCT
Tiltable	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel & Antique Brass Only)

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	696g
Inrush Current	60A 0.037ms
Cut Out Size	80-85
Construction Material	Stainless steel 316 (top) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL038DWBM40	Stainless steel 316	Stainless Steel	2.9W	4000K	40°	300	103	563	A D
GL038AWBM27	Antique brass	Antique Brass	2.9W	2700K	40°	280	96	526	A E
GL038AWBM30	Antique brass	Antique Brass	2.9W	3000K	40°	290	100	544	A E

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

### ACCESSORIES

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

BEAM ANGLE: **40°**

