

**2.9W** 2.9W

**Coastal protected**

**AC** Mains voltage groundlight

## WARRANTY

Warranty 7 years

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Marine grade stainless steel 316 or antique brass

Long lifetime of 70,000hrs

## GL038

2.9W, 300lm ground light

### FEATURES

|                        |             |
|------------------------|-------------|
| IP rating              | IP65        |
| IK rating              | IK06        |
| CSP Switchable         | Single CCT  |
| Tiltable (°)           | Fixed       |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>80      |
| Colour Consistency     | SDCM3       |
| Walk Over / Drive Over | No          |

### INSTALLATION INFORMATION

|                             |  |
|-----------------------------|--|
| Input                       | 220-240V AC                                  |
| Maximum Ambient Temperature | 35°C   |
| Weight                      | 696g   |
| Inrush Current              | 60A 0.037ms                                  |
| Cut Out Size                | 80-85  |
| Construction Material       | Stainless steel 316 (top) / aluminium (body) |
| UK Bathroom Zone            | 2  |
| SELV                        | Yes  |
| Electric Class (1, 2, 3)    | I  |
| Earth Leakage               | 0.1  |
| Suitable for coastal areas  | Yes  |

### PHOTOMETRICS @ 25°C

| Product code | Finish              | Type            | W    | Colour | Beam | lm  | lm/W | Lx @ 1m | Energy |
|--------------|---------------------|-----------------|------|--------|------|-----|------|---------|--------|
| GL038DWBM40  | Stainless steel 316 | Stainless Steel | 2.9W | 4000K  | 40°  | 300 | 103  | 563     | A D    |
| GL038AWBM27  | Antique brass       | Antique Brass   | 2.9W | 2700K  | 40°  | 280 | 96   | 526     | A E    |
| GL038AWBM30  | Antique brass       | Antique Brass   | 2.9W | 3000K  | 40°  | 290 | 100  | 544     | A E    |

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

|                         |   |
|-------------------------|---|
| Cable / Flying Lead     | 1m H05RN-F rubberised cable (outside diameter: 7mm) |
| Type of Wiring Required | Parallel  |
| Input Cable Type        | H05RN-F (7MM OD) 3 CORE                             |

### LED DRIVER

| Driver                       | Input    | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes  | No      | 2             |

### ACCESSORIES

|                   |                                 |                 |
|-------------------|---------------------------------|-----------------|
| Installation Tube | For easy ground installation    | Included        |
| JB5               | Gel filled waterproof connector | Sold Separately |
| WC 5-9            | Quick waterproof connector      | Sold Separately |

BEAM ANGLE: **40°**

