



GL040 LOW GLARE

Low Glare Ground Light

FEATURES

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	150mA / 250mA / 350mA / 500mA / 700mA DC
Maximum Ambient Temperature	55°C
Weight	GL040AB: 700g, GL040BK: TBC, GL040SS: 818g
Inrush Current	N/A
Cut Out Size	70mm
Construction Material	Stainless Steel
UK Bathroom Zone	1
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A
PSMD70024	220-240V	Yes	Yes	N/A

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

- IP68** IP68 perfect for internal or external applications
- Coastal protected**
- IK08** IK08 impact protection - walk over (Stainless Steel only)

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

- Supplied complete with installation tube
- SDCM3 ensuring uniform light appearance and consistency
- Single LED and lens combination for maximum efficiency and optimal light distribution
- CRI 80 providing true colour appearance

