



**IP68**



**IK08**

IK08 impact protection -  
walk over (Stainless Steel  
only)

## GL040 LOW GLARE

Low Glare Ground Light

### FEATURES

<b>IP rating</b>	IP68
<b>IK rating</b>	IK08
<b>CSP Switchable</b>	Single CCT
<b>Tiltable</b>	No
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over (Stainless Steel & Antique Brass Only)

### INSTALLATION INFORMATION

<b>Input</b>	150mA / 250mA / 350mA / 500mA / 700mA
<b>Maximum Ambient Temperature</b>	55°C
<b>Weight</b>	GL040AB: 700g, GL040BK: TBC, GL040SS: 818g
<b>Inrush Current</b>	N/A
<b>Cut Out Size</b>	70mm
<b>Construction Material</b>	Stainless Steel
<b>UK Bathroom Zone</b>	1
<b>SELV</b>	N/A
<b>Electric Class (1, 2, 3)</b>	3
<b>Earth Leakage</b>	N/A
<b>Suitable for coastal areas</b>	Yes

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
DRV150700 (all settings)	220-240V	Yes	No	N/A
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A
PSMD70024	220-240V	Yes	Yes	N/A

### ACCESSORIES

<b>JB2 / JB4 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately

BEAM ANGLE: **12°**

