



Stainless Steel



Antique Brass



Black

GL040 ULTRA LOW GLARE

Ultra Low Glare Ground Light

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Tiltable (°) | Fixed |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

INSTALLATION INFORMATION

| | |
|-----------------------------|---|
| Input | 150mA / 250mA / 350mA / 500mA DC |
| Maximum Ambient Temperature | 55°C |
| Weight | GL040AB: 940g, GL040BK: 430g, GL040SS: 880g |
| Inrush Current | N/A |
| Cut Out Size | 70mm |
| Construction Material | Stainless Steel |
| UK Bathroom Zone | 1 |
| SELV | N/A |
| Electric Class (1, 2, 3) | III |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone |
|-------------------------|----------|------|---------|---------------|
| DRV150700 (150-500mA) | 220-240V | Yes | No | N/A |
| DRV350700TD (350-500mA) | 220-240V | Yes | Yes | N/A |
| PSIP35018W | 220-240V | Yes | No | 1 |

ACCESSORIES

| | | |
|-----------------|----------------------------|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| WCR 275 BLACK | 2-core rubber cable | Sold Separately |

- IP68** IP68 perfect for internal or external applications
- Coastal protected**
- IK08** IK08 impact protection - walk over (Stainless Steel only)

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

- Supplied complete with installation tube
- SDCM3 ensuring uniform light appearance and consistency
- Single LED and lens combination for maximum efficiency and optimal light distribution
- CRI 80 providing true colour appearance

