



2W at 350mA



Baffled for low glare and visual comfort

Low voltage ground light

GL040 ULG

2W, 215lm ground light

Features

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
UGR	10
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	0.7
Inrush Current	N/A
Cut Out Size	70
Construction Material	Brass
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Single LED and lens combination for maximum efficiency and optimal light distribution
- Marine grade stainless steel 316 or antique brass
- Long lifetime of 70,000hrs

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL040AMBL27	Antique brass	2W	2700K	34°	200	100	645	
GL040AMBL30	Antique brass	2W	3000K	34°	208	104	671	
GL040ANBL27	Antique brass	2W	2700K	12°	200	100	2689	
GL040ANBL30	Antique brass	2W	3000K	12°	208	104	2797	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	4
PSIP3509W	220-240V	Yes	No	0	1	4
PSMD35039	220-240V	Yes	Yes (mains)	0	2	4

Accessories

JB2 / JB4 / JB6	IP68 Boxes	Sold Separately
TUBE/68	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

