

2W

2W at 350mA



Baffled for low glare and visual comfort



Low voltage ground light

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution

Marine grade stainless steel 316 or antique brass

Long lifetime of 70,000hrs

PATENT: [GB2544975 EP3176502](#)

GL040 ULG

2W, 215lm ground light

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Tiltable (°) | Fixed |
| UGR | UGR<16 |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | No |

INSTALLATION INFORMATION

| | |
|-----------------------------|----------|
| Input | 350mA DC |
| Maximum Ambient Temperature | 35°C |
| Weight | 0.7 |
| Inrush Current | N/A |
| Cut Out Size | 70 |
| Construction Material | Brass |
| UK Bathroom Zone | 1 |
| Electric Class (1, 2, 3) | III |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------|----|--------|------|-----|------|---------|--------|
| GL040AMBL27 | Antique brass | 2W | 2700K | 34° | 200 | 100 | 645 | |
| GL040AMBL30 | Antique brass | 2W | 3000K | 34° | 208 | 104 | 671 | |
| GL040ANBL27 | Antique brass | 2W | 2700K | 12° | 200 | 100 | 2689 | |
| GL040ANBL30 | Antique brass | 2W | 3000K | 12° | 208 | 104 | 2797 | |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | H05RN-F (6MM OD) 2 CORE |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-----------|----------|------|---------|---------------|-----|-----|
| PSIP3509W | 220-240V | Yes | No | 0 | 1 | 4 |

ACCESSORIES

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | IP68 Boxes | Sold Separately |
| TUBE/68 | Installation tube | Sold Separately |
| PDC/GRID DIMMER | Grid dimmer kit for multiple fitting types | Sold Separately |

34°

