



2W at 350mA



Baffled for low glare and visual comfort

Low voltage ground light

GL040 Ultra low-glare

2W, 215lm ground light

Features

| | |
|------------------------|-------------|
| IP rating | IP68 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| UGR | 10 |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

Installation Information

| | |
|-----------------------------|-----------------------|
| Input | 350mA / 700mA |
| Maximum Ambient Temperature | 35°C |
| Weight | 818g |
| Inrush Current | N/A |
| Cut Out Size | 70 |
| Construction Material | Stainless steel (316) |
| UK Bathroom Zone | 1 |
| Electric Class (1, 2, 3) | 3 |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Guarantee

Warranty 7 years

Features & benefits

- Perfect for both interior and exterior applications
- Compliments environments with ultra low glare up-lighting effect
- marine-grade stainless steel 316

Photometrics @ 25°C

| Product Code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|-----------------|----|--------|------|-----|------|---------|--------|
| GL040DNBL40 | Stainless steel | 2W | 4000K | 12° | 215 | 108 | 2891 | |
| GL040DMBL40 | Stainless steel | 2W | 4000K | 34° | 215 | 108 | 694 | |
| GL040DNBL30 | Stainless steel | 2W | 3000K | 12° | 208 | 104 | 2797 | |
| GL040DMBL30 | Stainless steel | 2W | 3000K | 34° | 208 | 104 | 671 | |
| GL040DNBL27 | Stainless steel | 2W | 2700K | 12° | 200 | 100 | 2689 | |
| GL040DMBL27 | Stainless steel | 2W | 2700K | 34° | 200 | 100 | 645 | |

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | H05RN-F (6MM OD) 2 CORE |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-------------|----------|------|-------------|---------------|-----|-----|
| PLU/350 1-9 | 220-240V | Yes | No | 0 | 1 | 4 |
| PSIP3509W | 220-240V | Yes | No | 0 | 1 | 4 |
| PSMD35039 | 220-240V | Yes | Yes (mains) | 0 | 2 | 4 |

Accessories

| | | |
|-----------------|----------------------------|-----------------|
| JB2 / JB4 / JB6 | IP68 waterproof connectors | Sold Separately |
| TUBE/68 | Installation tube | Sold Separately |
| GLA01 | Square transformer plate | Sold Separately |

