



collingwood



2W at 350mA



Baffled for low glare and visual comfort

Low voltage ground light

GL040 Ultra low-glare

2W, 215lm ground light

Features

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
UGR	10
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA / 700mA
Maximum Ambient Temperature	35°C
Weight	818g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Perfect for both interior and exterior applications
- Compliments environments with ultra low glare up-lighting effect
- marine-grade stainless steel 316

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL040DNBL40	Stainless steel	2W	4000K	12°	215	108	2891	AIG D
GL040DMBL40	Stainless steel	2W	4000K	34°	215	108	694	AIG D
GL040DNBL30	Stainless steel	2W	3000K	12°	208	104	2797	AIG E
GL040DMBL30	Stainless steel	2W	3000K	34°	208	104	671	AIG E
GL040DNBL27	Stainless steel	2W	2700K	12°	200	100	2689	AIG E
GL040DMBL27	Stainless steel	2W	2700K	34°	200	100	645	AIG E

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	4
PSIP3509W	220-240V	Yes	No	0	1	4
PSMD35039	220-240V	Yes	Yes (mains)	0	2	4

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
GLA01	Square transformer plate	Sold Separately

