



## GL040CARGB

Colour change LED ground light (3.5W max.)

### Features

IP rating	IP67
IK rating	IK08
CSP Switchable	RGB
LED Lifetime	L50 50,000h
Walk Over / Drive Over	Walk over

### Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	800g
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

### RGB Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
GL040CARGB	1W	Red	18°	34	34	287
GL040CARGB	1.2W	Green	18°	68	56	697
GL040CARGB	1.2W	Blue	18°	8	7	8

### Wiring Information

Cable / Flying Lead	2x 1m LED RGB 0.75mm <sup>2</sup> cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F 4 CORE, 6MM OD

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	13
CCDRV75DMX	220-240V	Yes	Yes	2	13
CCDRV75RF	220-240V	Yes	Yes	2	13

### Accessories

TUBE/68	Installation tube	Sold Separately
JB7	5-pole IP68 inline connector	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately
GLA01	Ground Light Accessory, square plate, stainless steel 316	Sold Separately



RGB



Coastal protected



IK08 suitable for pathways

### Guarantee

Warranty 5 years

### Features & benefits

- Low profile for easy installation
- Installation tube available
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments

