



## GL040 ULTRA LOW GLARE

2W, 215lm ground light

### FEATURES

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Tilttable (°)	Fixed
UGR	UGR<16
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

### INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	35°C
Weight	818g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL040DNBL40	Stainless steel	2W	4000K	12°	215	108	2891	
GL040DMBL40	Stainless steel	2W	4000K	34°	215	108	694	
GL040DNBL30	Stainless steel	2W	3000K	12°	208	104	2797	
GL040DMBL30	Stainless steel	2W	3000K	34°	208	104	671	
GL040DNBL27	Stainless steel	2W	2700K	12°	200	100	2689	
GL040DMBL27	Stainless steel	2W	2700K	34°	200	100	645	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	0	1	4

### ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

marine-grade stainless steel 316

PATENT: **GB2544975 EP3176502**BEAM ANGLE: **12°**