



GL040 ULTRA LOW GLARE

2W, 215lm ground light

FEATURES

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Tiltable (°)	Fixed
UGR	UGR<16
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	35°C
Weight	818g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL040DNBL40	Stainless steel	2W	4000K	12°	215	108	2891	D
GL040DMBL40	Stainless steel	2W	4000K	34°	215	108	694	D
GL040DNBL30	Stainless steel	2W	3000K	12°	208	104	2797	E
GL040DMBL30	Stainless steel	2W	3000K	34°	208	104	671	E
GL040DNBL27	Stainless steel	2W	2700K	12°	200	100	2689	E
GL040DMBL27	Stainless steel	2W	2700K	34°	200	100	645	E

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	0	1	4

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

COLLINGWOOD LIGHTING

LIGHTING INNOVATION

2W at 350mA

Baffled for low glare and visual comfort

Low voltage ground light

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

marine-grade stainless steel 316

PATENT: **GB2544975 EP3176502**

BEAM ANGLE: **12°**

