



GL045

8W, 610lm walk over ground light



8W



Coastal protected



Mains voltage ground light

Features

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
UGR	10
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Walk Over / Drive Over	Walk over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	917g
Inrush Current	20A 0.5ms
Cut Out Size	120
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

Guarantee

Warranty 5 years

Features & benefits

- 120mm cut out diameter
- A narrow beam angle of 20° for a more focused light
- High impact rating of IK08
- High light output of 610 lumens
- Low glare UGR <10

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL045X30	Stainless steel	8.1W	3000K	20°	610	75	2924	

Wiring Information

Cable / Flying Lead	160mm H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	N/A	2	N/A	N/A

Accessories

JB5	IP68 waterproof connector	Sold Separately
WCR375BLACK	3-core rubber cable	Sold Separately
Installation Tube	Diameter: 120mm, Depth: 105mm	Included

