



3W at 350mA



Frosted effect for low glare and soft lighting



Low voltage ground light

## GL050

3W, 50lm marker ground light

### FEATURES

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

### INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	552g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Earth Leakage	N/A
Suitable for coastal areas	Yes

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Robust cable for outdoor use

Brushed steel finish for sleek effect

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL050 NW	Stainless steel	3W	4000K	100°	50	17	20	
GL050 WARM WHITE	Stainless steel	3W	3000K	100°	46	15	16	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series


### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	0	1	2

### ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

BEAM ANGLE: **100°**



Ø76mm

