



collingwood



3W at 350mA



Frosted effect for low glare and soft lighting

Low voltage ground light

GL050

3W, 50lm marker ground light

Features

IP rating	IP68
IK rating	IK08
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	552g
Inrush Current	N/A
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Robust cable for outdoor use
- Brushed steel finish for sleek effect

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL050 NW	Stainless steel	3W	4000K	100°	50	17	20	
GL050 WW	Stainless steel	3W	3000K	100°	46	15	16	
GL050 27	Stainless steel	3W	2700K	100°	46	15	16	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	3
PSIP3509W	220-240V	Yes	No	0	1	2
PSMD35039	220-240V	Yes	Yes (mains)	0	1	3

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately

