



## GL050

3W, 50lm marker ground light

### FEATURES

<b>IP rating</b>	IP68
<b>IK rating</b>	IK08
<b>CSP Switchable</b>	Single CCT
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over (Stainless Steel & Antique Brass Only)

### INSTALLATION INFORMATION

<b>Input</b>	350mA
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	552g
<b>Inrush Current</b>	N/A
<b>Cut Out Size</b>	70
<b>Construction Material</b>	Stainless steel (316)
<b>UK Bathroom Zone</b>	0
<b>Electric Class (1, 2, 3)</b>	3
<b>Earth Leakage</b>	N/A
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL050 NW	Stainless steel	3W	4000K	100°	50	17	20	
GL050 WW	Stainless steel	3W	3000K	100°	46	15	16	
GL050 27	Stainless steel	3W	2700K	100°	46	15	16	

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	H05RN-F (6MM OD) 2 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	3
PSIP3509W	220-240V	Yes	No	0	1	2
PSMD35039	220-240V	Yes	Yes (mains)	0	1	3

### ACCESSORIES

<b>JB2 / JB4 / JB6</b>	IP68 waterproof connectors	Sold Separately
<b>TUBE/68</b>	Installation tube	Sold Separately
<b>WCR 275 BLACK</b>	2-core rubber cable	Sold Separately
<b>PDC/GRID DIMMER</b>	Grid dimmer kit for multiple fitting types	Sold Separately



3W at 350mA



Frosted effect for low glare and soft lighting



Low voltage ground light

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Robust cable for outdoor use

Brushed steel finish for sleek effect

