



collingwood



3W at 350mA



Coastal protected

Low voltage ground light

GL063

3W, 45lm 3 way ground light

Features

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	No

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	1.165Kg
Inrush Current	N/A
Cut Out Size	55
Construction Material	Cast stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Cast stainless steel for aged effect
- Raised profile sending light in three directions

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	lm	lm/W	Lx @ 1m	Energy
GL063	Stainless steel	4 Windows	3W	3000K	45	15	9	

Wiring Information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	H05RN-F (6MM OD) 2 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	3
PSIP3509W	220-240V	Yes	No	0	1	2
PSMD35039	220-240V	Yes	Yes (mains)	0	1	3

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE/68	Installation tube	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

Beam angle:

