



GL06

21W, 970lm straight to mains drive over ground light

Features

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
UGR	10
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Walk Over / Drive Over	Drive over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	3.7kg
Inrush Current	10A 0.5ms
Cut Out Size	196
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL06X30	Stainless steel 316	21W	3000K	20°	970	46	6203	

Wiring Information

Cable / Flying Lead	300mm H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	N/A	2	N/A	N/A

Accessories

JB5	IP68 waterproof connector	Sold Separately
WCR375BLACK	3-core rubber cable	Sold Separately



collingwood



21W



Coastal protected



Mains voltage ground light

Guarantee

Warranty 5 years

Features & benefits

- Ideal for commercial and residential lighting, drive ways, perimeters and large trees
- Marine-grade stainless steel 316
- 196mm cut out
- High lumen output of 620lm
- A narrow beam angle of 20° for a more focused light
- Low glare UGR <10

