



21W



Coastal protected



Mains voltage ground light

GL06

21W, 970lm straight to mains drive over ground light

Features

IP rating	IP67
IK rating	IK08
CSP Switchable	Single CCT
UGR	UGR<16, UGR<19, UGR<22
LED Lifetime	L70 30,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Walk Over / Drive Over	Drive over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	3.7kg
Inrush Current	10A 0.5ms
Cut Out Size	196
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 5 years

Features & benefits

- Ideal for commercial and residential lighting, drive ways, perimeters and large trees
- Marine-grade stainless steel 316
- 196mm cut out
- High lumen output of 620lm
- A narrow beam angle of 20° for a more focused light
- Low glare UGR <10

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL06X30	Stainless steel 316	21W	3000K	20°	970	46	6203	

Wiring Information

Cable / Flying Lead	300mm H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	N/A	2	N/A	N/A

Accessories

JB5	IP68 waterproof connector	Sold Separately
WCR375BLACK	3-core rubber cable	Sold Separately

