



8.5W



Coastal protected



Mains voltage ground light

## GL07

8.5W, 695lm drive over LED ground light

### Features

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable	20°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	2.8Kg
Inrush Current	0.92A 0.13ms
Cut Out Size	N/A
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes
Power Factor	0.90

### Guarantee

Warranty 5 years

### Features & benefits

- Adjustable LED fittings
- High lumen output of 695lm
- Robust cable for outdoor use
- Installation tube included
- Ideal for driveways with 10mm toughened glass

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL07D38X40	Stainless steel 316	8.5W	4000K	38°	695	82	1620	
GL07D24X40	Stainless steel 316	8.5W	4000K	24°	695	82	2198	
GL07D60X30	Stainless steel 316	8.5W	3000K	60°	695	82	550	
GL07D38X30	Stainless steel 316	8.5W	3000K	38°	695	82	1620	
GL07D24X30	Stainless steel 316	8.5W	3000K	24°	695	82	2198	

### Wiring Information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (driver built in)	220-240V	Yes	No	2	-	-

### Accessories

Installation tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

