

8.5W 8.5W

Coastal protected

AC Mains voltage ground light

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

- Adjustable LED fittings
- High lumen output of 695lm
- Robust cable for outdoor use
- Installation tube included
- Ideal for driveways with 10mm toughened glass



GL07

8.5W, 695lm drive over LED ground light

FEATURES

| | |
|------------------------|----------------------------|
| IP rating | IP67 |
| IK rating | IK10 |
| CSP Switchable | Single CCT |
| Tilttable (°) | 20 |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Drive over (15mph maximum) |

INSTALLATION INFORMATION

| | |
|-----------------------------|---|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 2.8Kg |
| Inrush Current | 0.92A 0.13ms |
| Cut Out Size | N/A |
| Construction Material | Stainless steel 316 (cover ring) / aluminium (body) |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | I |
| Earth Leakage | 0.1 |
| Suitable for coastal areas | Yes |
| Power Factor | 0.90 |

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|---------------------|------|--------|------|-----|------|---------|--------|
| GL07D24X40 | Stainless steel 316 | 8.5W | 4000K | 24° | 695 | 82 | 2198 | |
| GL07D38X30 | Stainless steel 316 | 8.5W | 3000K | 38° | 695 | 82 | 1620 | |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m H05RN-F rubberised cable (outside diameter: 7mm) |
| Type of Wiring Required | Parallel |
| Input Cable Type | H05RN-F (7MM OD) 3 CORE |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|-----------------------|----------|------|---------|---------------|-----|-----|
| N/A (driver built in) | 220-240V | Yes | No | 2 | - | - |

ACCESSORIES

| | | |
|-------------------|---------------------------------|-----------------|
| Installation tube | For easy ground installation | Included |
| JB5 | Gel filled waterproof connector | Sold Separately |
| WC 5-9 | Quick waterproof connector | Sold Separately |

