



17W

Coastal protected

Mains voltage ground light

## GL08

17W, 1,390lm drive over ground light

### Features

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tilttable	20°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.1Kg
Inrush Current	1.8A 0.2ms
Cut Out Size	N/A
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Suitable for coastal areas	Yes

### Guarantee

### Features & benefits

- Adjustable LED fittings
- Robust cable for outdoor use
- Installation tube included
- Ideal for driveways with 10mm toughened glass

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL08D60X30	Stainless steel 316	17W	3000K	60°	1390	82	1103	
GL08D38X30	Stainless steel 316	17W	3000K	38°	1390	82	3146	
GL08D24X30	Stainless steel 316	17W	3000K	24°	1390	82	4862	

### Wiring Information

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-

### Accessories

Installation tube	Included
JB5	Gel filled waterproof connector Sold Separately
WC 5-9	Quick waterproof connector Sold Separately

