



# GL08

17W, 1,390lm drive over ground light

#### **FEATURES**

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable (°)	20
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

#### INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	40°C		
Weight	4.1Kg		
Inrush Current	1.8A 0.2ms		
Cut Out Size	N/A		
Construction Material	Stainless steel 316 (cover		
	ring) / aluminium (body)		
UK Bathroom Zone	2		
SELV	Yes		
Electric Class (1, 2, 3)	T		
Suitable for coastal areas	Yes		

## PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL08D24X30	Stainless steel 316	17W	3000K	24°	1390	82	4862	Å F

## WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-

# **ACCESSORIES**

Installation tube		Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION

17W

Coastal protected

Mains voltage ground light

## FEATURES & BENEFITS

Adjustable LED fitting:

Robust cable for outdoor use

Installation tube included

Ideal for driveways with 10mm toughened glas