

17W

Coastal protected

Mains voltage ground light

FEATURES & BENEFITS

Adjustable LED fittings

Robust cable for outdoor use

Installation tube included

Ideal for driveways with 10mm toughened glass



GL08

17W, 1,390lm drive over ground light

FEATURES

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable (°)	20
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.1Kg
Inrush Current	1.8A 0.2ms
Cut Out Size	N/A
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL08D24X30	Stainless steel 316	17W	3000K	24°	1390	82	4862	

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

Installation tube	Included
JB5	Gel filled waterproof connector Sold Separately
WC 5-9	Quick waterproof connector Sold Separately

24°