

GL08

17W, 1,390Im drive over ground light

FEATURES

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable (°)	20
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.1Kg
Inrush Current	1.8A 0.2ms
Cut Out Size	N/A
Construction Material	Stainless steel 316 (cover
Construction Material	ring) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL08D24X30	Stainless steel 316	17W	3000K	24°	1390	82	4862	A F

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)			
Type of Wiring Required	Parallel			
Input Cable Type	H05RN-F (7MM OD) 3 CORE			

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zo	ne Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-
ACCESSORIES						
Installation tube	For easy ground installation			Included		
JB5	Gel filled waterproof connector			Sold Separately	/	
WC 5-9	Quick waterproof connector			Sold Separately		



LIGHTING INNOVATION

 17W

 Coastal protected

 Acc

 Mains voltage ground light

WARRANTY

ranty

5 yeai

FEATURES & BENEFITS

Adjustable LED fittings
Robust cable for outdoor use
Installation tube included
Ideal for driveways with 10mm toughened glass

Ø225/212mm

