



GL08

17W, 1,390lm drive over ground light

FEATURES

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable	20°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	4.1Kg
Inrush Current	1.8A 0.2ms
Cut Out Size	N/A
Construction Material	Stainless steel 316 (cover ring) / aluminium (body)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
GL08D38X30	Stainless steel 316	17W	3000K	38°	1390	82	3146	
GL08D24X30	Stainless steel 316	17W	3000K	24°	1390	82	4862	

WIRING INFORMATION

Cable / Flying Lead	1m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

Installation tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately



17W



Coastal protected



Mains voltage ground light

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Adjustable LED fittings

Robust cable for outdoor use

Installation tube included

Ideal for driveways with 10mm toughened glass

Ø225/212mm

