



5.7W



Coastal protected



Straight to mains ground light

GL200

5.7W, 40lm, domed ground light

Features

IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRi>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	940g
Inrush Current	31A 0.12ms
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Marine grade stainless steel 316 or antique brass
- 5 window styles and colour temperatures to suit any installation
- Drive over - suitable for use on driveways (with TUBE/68)

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GL200DXIX27	Stainless steel 316	1 Window	5.7W	2700K	90°	10	2	
GL200DXIX30	Stainless steel 316	1 Window	5.7W	3000K	90°	10	2	
GL200DXIX40	Stainless steel 316	1 Window	5.7W	4000K	90°	10	2	
GL200DX2127	Stainless steel 316	2 Windows 1 Direction	5.7W	2700K	90°	20	4	
GL200DX2130	Stainless steel 316	2 Windows 1 Direction	5.7W	3000K	90°	20	4	
GL200DX2140	Stainless steel 316	2 Windows 1 Direction	5.7W	4000K	90°	20	4	
GL200DX2227	Stainless steel 316	2 Windows 2 Directions	5.7W	2700K	90°	20	4	
GL200DX2230	Stainless steel 316	2 Windows 2 Directions	5.7W	3000K	90°	20	4	
GL200DX2240	Stainless steel 316	2 Windows 2 Directions	5.7W	4000K	90°	20	4	
GL200DX3X27	Stainless steel 316	3 Windows	5.7W	2700K	90°	30	5	

Wiring Information


Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (intergrated SELV driver)	220-240V	Yes	No	2	-	-

Accessories

JB5	Gell filled waterproof connector	Sold Separately
TUBE/68	Installation tube	Sold Separately



WC 5-9	Quick waterproof connector	Sold Separately
--------	----------------------------	-----------------



collingwood

The GL200 creates a grazing light effect from a domed, marine-grade stainless steel 316 housing. This product is available in five different window styles and three colour temperatures to suit a wide range of applications. This is ideal for providing low-glare illumination for decorative effect and safe navigation of driveways and car parks.