

**5.7W** 5.7W



Coastal protected



Straight to mains ground light

## WARRANTY

Warranty

7 years

## FEATURES & BENEFITS

Marine grade stainless steel 316 or antique brass

5 window styles and colour temperatures to suit any installation



## GL200

5.7W, 40lm, domed ground light

### FEATURES

IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	1060g
Inrush Current	31A 0.12ms
Cut Out Size	70
Construction Material	Brass
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GL200DX3X30	Stainless steel 316	3 Windows	5.7W	3000K	90°	30	5	A t G E
GL200DX4X27	Stainless steel 316	4 Windows	5.7W	2700K	90°	40	7	A t G E
GL200DX4X30	Stainless steel 316	4 Windows	5.7W	3000K	90°	40	7	A t G E
GL200DX4X40	Stainless steel 316	4 Windows	5.7W	4000K	90°	40	7	A t G D
GL200AX1X30	Antique brass	1 Window	5.7W	3000K	90°	10	2	A t G E
GL200AX2130	Antique brass	2 Windows 1 Direction	5.7W	3000K	90°	20	4	A t G E
GL200AX2230	Antique brass	2 Windows 2 Direction	5.7W	3000K	90°	20	4	A t G E
GL200AX3X30	Antique brass	3 Windows	5.7W	3000K	90°	30	5	A t G E
GL200AX4X30	Antique brass	4 Windows	5.7W	3000K	90°	40	7	A t G E

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

### ACCESSORIES

JB5	Gell filled waterproof connector	Sold Separately
TUBE/68	Installation tube	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

BEAM ANGLE: 90°

