



GL200

5.7W, 40lm, domed ground light

FEATURES

IP rating	IP65
IK rating	IK10
CSP Switchable	Single CCT
Tiltable (°)	Fixed
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	960g
Inrush Current	31A 0.12ms
Cut Out Size	70
Construction Material	Stainless steel (316)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GL200DXIX30	Stainless steel 316	1 Window	5.7W	3000K	90°	10	2	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	H05RN-F (7MM OD) 3 CORE

LED DRIVER


Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

JB5	Gell filled waterproof connector	Sold Separately
TUBE/68	Installation tube	Sold Separately
WC 5-9	Quick waterproof connector	Sold Separately

 5.7W

 Coastal protected

 Straight to mains ground light

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Marine grade stainless steel 316 or antique brass

5 window styles and colour temperatures to suit any installation

BEAM ANGLE: 90°

