

**5.7W** 5.7W



Coastal protected



Straight to mains ground light

## WARRANTY

Warranty

7 years

## FEATURES & BENEFITS

Marine grade stainless steel 316 or antique brass

5 window styles and colour temperatures to suit any installation



## GL200

5.7W, 40lm, domed ground light

### FEATURES

<b>IP rating</b>	IP65
<b>IK rating</b>	IK10
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	Fixed
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Walk Over / Drive Over</b>	Walk over

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	940g
<b>Inrush Current</b>	31A 0.12ms
<b>Cut Out Size</b>	70
<b>Construction Material</b>	Stainless steel (316)
<b>UK Bathroom Zone</b>	2
<b>SELV</b>	Yes
<b>Electric Class (1, 2, 3)</b>	I
<b>Earth Leakage</b>	0.1
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GL200DX2140	Stainless steel 316	2 Windows 1 Direction	5.7W	4000K	90°	20	4	
GL200DX2227	Stainless steel 316	2 Windows 2 Directions	5.7W	2700K	90°	20	4	
GL200DX2230	Stainless steel 316	2 Windows 2 Directions	5.7W	3000K	90°	20	4	
GL200DX2240	Stainless steel 316	2 Windows 2 Directions	5.7W	4000K	90°	20	4	
GL200DX3X27	Stainless steel 316	3 Windows	5.7W	2700K	90°	30	5	
GL200DX3X30	Stainless steel 316	3 Windows	5.7W	3000K	90°	30	5	
GL200DX4X27	Stainless steel 316	4 Windows	5.7W	2700K	90°	40	7	
GL200DX4X30	Stainless steel 316	4 Windows	5.7W	3000K	90°	40	7	
GL200DX4X40	Stainless steel 316	4 Windows	5.7W	4000K	90°	40	7	
GL200AX1X30	Antique brass	1 Window	5.7W	3000K	90°	10	2	

Energy rating is a reflection of the LED light source.

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	3m H05RN-F rubberised cable (outside diameter: 7mm)
<b>Type of Wiring Required</b>	Parallel
<b>Input Cable Type</b>	H05RN-F (7MM OD) 3 CORE

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

### ACCESSORIES

<b>JB5</b>	Gell filled waterproof connector	Sold Separately
<b>TUBE/68</b>	Installation tube	Sold Separately
<b>WC 5-9</b>	Quick waterproof connector	Sold Separately

