

IP67

IP67 for complete protection against ingress of dust & water

IK10

IK08 (GLTM_11/14) IK10 (GLTM_16/19/22)



Suitable for coastal applications

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

Tilt angle of luminaire is adjustable, just turn knob to tilt the light distribution up to 25 degrees

Static loading capacity is 2000kg

Pre-wired with 1 meter of cable to aid the installer

DALI-2 dimmable and RGBW options also available

Supplied with installation tube



TILT ADJUSTABLE GROUND LIGHT

Straight to Mains, TRIAC mains dimmable

FEATURES

IP rating	IP67
IK rating	IK10
CSP Switchable	Single CCT
Tiltable	25°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Drive over (15mph maximum)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-25°C - 40°C
Weight	GLTM_11: 0.99kg, GLTM_14: 1.56kg, GLTM_16: 2.03kg, GLTM_19: 3.26kg, GLTM_22: 3.98kg
Inrush Current	GLTM_11: 0.5A 0.4ms, GLTM_14: 0.6A 0.4ms, GLTM_16: 0.45A 0.5ms, GLTM_19: 0.55A 0.5ms, GLTM_22: 0.55A 0.5ms
Cut Out Size	223
Construction Material	Anodised aluminium body, 316 SS bezel
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
GLTMS119T30	Stainless steel 316	Ø119mm cut-out	6W	3000K	34°	450	75	
GLTMS147T30	Stainless steel 316	Ø147mm cut-out	12W	3000K	34°	1200	100	
GLTMF147T30	Stainless steel 316	Ø147mm cut-out	12W	3000K	60°	1200	100	
GLTMS165T30	Stainless steel 316	Ø165mm cut-out	18W	3000K	34°	1600	89	
GLTMF165T30	Stainless steel 316	Ø165mm cut-out	18W	3000K	60°	1600	89	
GLTMS193T30	Stainless steel 316	Ø193mm cut-out	23W	3000K	34°	2300	100	
GLTMS223T30	Stainless steel 316	Ø223mm cut-out	30W	3000K	34°	3300	100	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	Pre-wired 1.0M H05RN-F, 3x1.0mm ²
Type of Wiring Required	Parallel

ACCESSORIES

DM298FP	Faceplate rotary mains dimmer	Sold Separately
DM298GRID	Grid rotary mains dimmer	Sold Separately
JB5	Gel filled waterproof connector	Sold Separately

BEAM ANGLE: 34°

