



Colour switchable between 2700K, 3000K and 4000K

Wattage switchable between 4.2W & 6W

Switches allow you to choose options at installation

## H2 Lite CSP

Fixed, fire rated downlight, colour switchable via switch under the bezel

### Features

IP rating	IP65
CSP Switchable	Switchable CCT
UGR	26
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3
Emergency Option	No

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	166g
Insulation Coverable	Rolled and blown insulation
Inrush Current	5A 0.15ms
Cut Out Size	Ø 64-72mm
Construction Material	Mild steel / V0 rated plastic
UK Bathroom Zone	1
Maximum ceiling thickness	40 mm
Suitable for coastal areas	No
Install Connector Type	Integrated push-fit terminal connector
UK Building Regulations	Part B, C, E, P & L
FR Building Regulations	RE2020, EN 13141-1:2004, EN 1365-2:2014, EN ISO 10140-2/3:2010

### Guarantee

### Features & benefits

- High efficacy of 124lm/W
- 2-part connector provides first fix wiring whilst the luminaire is detached from the connector, loop in loop out, quick maintenance should disconnection/reconnection be required
- Compatible with Click Flow CT100 series
- TRIAC Mains dimmable
- Fixed with 55 degree beam angle
- Compatible with H2 Twist and lock bezels
- Control wirelessly from your phone or tablet using Collingwood Smart

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	Energy
DLT551500ABK	Black bezel included	Single unit	55°	4.2W	2700K	450	107	409	A t G D
					3000K	520	124	472	
					4000K	500	119	454	
				6W	2700K	625	104	409	
					3000K	720	120	472	
					4000K	700	117	454	
DLT551500ABS	Brushed steel bezel included	Single unit	55°	4.2W	2700K	450	107	409	A t G D
					3000K	520	124	472	
					4000K	500	119	454	
				6W	2700K	625	104	409	
					3000K	720	120	472	
					4000K	700	117	454	
DLT551500A	White bezel included	Single unit	55°	4.2W	2700K	450	107	409	A t G D
					3000K	520	124	472	
					4000K	500	119	454	
				6W	2700K	625	104	409	
					3000K	720	120	472	
					4000K	700	117	454	

Product not suitable for exterior use, please use H2 Pro Extreme.

### Wiring Information

Type of Wiring Required	Parallel
-------------------------	----------



### LED Driver

Driver	Input	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes (mains)	1 (Ceiling only)

### Accessories

H2 Bezels	Twist and lock bezels	Sold Separately
DLCVT110	Concealer ring for larger cut outs	Sold Separately

Beam angle: 55°



## Downlights specification sheet

<b>Collingwood Smart System</b>	Accessories to upgrade to smart	Sold Separately
<b>DM298FP</b>	Faceplate dimmer	Sold Separately
<b>DM298GRID</b>	Grid dimmer	Sold Separately



collingwood

The H2 Lite CSP is a superior solution that is engineered to be the perfect fit-and-forget solution. The colour temperature can be easily controlled by simply twisting the bezel off and flicking the switch on the front face of the product. The addition of the 2700K colour temperature gives you the option of creating an excellent and warm atmosphere. Large piano key terminals allow loop-in/ loop-out wiring with ease.