Downlights specification sheet



H4 Pro

70,000hrs long lifetime fire-rated downlight with detachable driver for easy repair/upgrade

Features				
IP rating	IP65			
CSP Switchable	Switchable CCT			
UGR	28			
Dimmable Option	Yes			
LED Lifetime	L70 70,000h			
Colour Rendering Index	CRI>80			
Colour Consistency	SDCM3			
Emergency Option	Yes			

Installation Information				
Input	220-240V AC			
Maximum Ambient Temperature	40°C			
Weight	270g			
Insulation Coverable	Rolled and blown insulation			
Inrush Current	1A 7.5ms			
Cut Out Size	Ø 69-72mm			
Construction Material	Mild steel / V0 rated plastic			
UK Bathroom Zone	1			
Maximum ceiling thickness	40 mm			
SELV	SELV			
Electric Class (1, 2, 3)	2			
Suitable for coastal areas	No			
Install Connector Type	Easy-fit connector			
UK Building Regulations	Part B, C, E, P & L			
	RE2020, EN 13141-1:2004, EN			
FR Building Regulations	1365-2:2014, EN ISO 10140-			
	2/3:2010			
Coiling Joint Approvals	Solid timber, I-Joist and			
Ceiling Joist Approvals	Metal Web			

Photometrics @ 25°C

Product Code	Finish	Туре	Beam	W	Colour	lm	lm/W	lx@1m	Energy
					2700K	550	110	554	
		Switchable		5W	3000K	650	130	654	
DLE5295500	Bezel sold	wattage &			4000K	650	130	654	A D
separately switchable CCT	switchable	switchable	7W	2700K	750	107	554	A D	
	CCT			3000K	850	121	654		
			4000K	850	121	654			

Product not suitable for exterior use, please use H2 Pro Extreme.

Wiring Information

_	
Cable / Flying Lead	0.15m
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel

LED Driver

Input		
220-240V		

Accessories

DLCVT110	Downlight Converter Plate	Sold Separately
DLCONVERT70	Downlight Converter Plate	Sold Separately
DM298FP	Faceplate Dimmer	Sold Separately
DM298GRID	Grid Dimmer	Sold Separately
Collingwood Smart System	Range available to turn the ordinary extraordinary	Sold Separately
H4 Pro Bezels	Twist & lock system makes changing bezels quick, clean and easy	Sold Separately
LEDEP11	Emergency kit	Sold Separately



Colour switchable between 2700K, 3000K and 4000K

Wattage switchable between 5W or 7W

Insulation coverable

Guarantee

Features & benefits

- 🛮 20° adjustable downlight
- Compatible with twist and lock bezels
- High efficacy of 130lm/W
- Compatible with Collingwood smart system
- Emergency option available
- 2 part, push fit, loop in/ loop out connector
- Flexible driver position for lower profile
- Mains dimmable





