





H5 TRIMLESS

Plaster-in, trimless, dimmable, fire-rated downlight

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
UGR	UGR<16
Sensor Option	No
Dimmable Option	Yes
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	No
Rotation Angle	No

INSTALLATION INFORMATION

Input	220-240V AC	
Maximum Ambient Temperature	40°C	
Weight	240g	
Insulation Coverable	Rolled and blown insulation	
Inrush Current	0.9A 0.05ms	
Cut Out Size	60-72	
Construction Material	Mild steel / VO rated plastic	
UK Bathroom Zone	1	
Maximum ceiling thickness	40 mm	
SELV	Yes	
Electric Class (1, 2, 3)	2	
Suitable for coastal areas	No	
Install Connector Type	Easy-fit connector	
UK Building Regulations	Part B, C, E, P & L	
	RE2020, EN 13141-1:2004, EN	
FR Building Regulations	1365-2:2014, EN ISO 10140-	
	2/3:2010	
UK Protection	Over Voltage, Short Circuit,	
OK Protection	Thermal	
David B Eiro Batina	Solid Timber 30/60/90min, I-	
Part B Fire Rating	Joist 30min	
Power Factor	0.90	

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
DL282WHNWDI	Matt white	Standard	6W	4000K	38°	650	108	1391	A D
DL282WHWWDI	Matt white	Standard	6W	3000K	38°	600	100	1284	A D

WIRING INFORMATION

Cable / Flying Lead	0.15m (Class II, complete with Easy-Fit connector)		
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)		
Type of Wiring Required	Parallel		
Input Cable Type	H03VVH2-F (2 CORE 0.75MM)		

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	Yes (mains)	1 (Ceiling only)	N/A	N/A

ACCESSORIES

DM298FP	Faceplate dimmer	Sold Separately
DM298GRID	Grid dimmer	Sold Separately



LIGHTING INNOVATION



Quick and easy installation



High efficacy of 108lm/W



Insulation coverable

WARRANTY

FEATURES & BENEFITS

When using a converter plate, the IP rating is not affected; however, the product is no longer

PATENT: **GB2487912 GB2512715**

