





H5 TRIMLESS

Plaster-in, trimless, dimmable, fire-rated downlight

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
UGR	UGR<16
Sensor Option	No
Dimmable Option	Yes
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Emergency Option	No
Rotation Angle	No

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	40°C		
Weight	240g		
Insulation Coverable	Rolled and blown insulation		
Inrush Current	0.9A 0.05ms		
Cut Out Size	60-72		
Construction Material	Mild steel / VO rated plastic		
UK Bathroom Zone	1		
Maximum ceiling thickness	40 mm		
SELV	Yes		
Electric Class (1, 2, 3)	2		
Suitable for coastal areas	No		
Install Connector Type	Easy-fit connector		
UK Building Regulations	Part B, C, E, P & L		
	RE2020, EN 13141-1:2004, EN		
FR Building Regulations	1365-2:2014, EN ISO 10140-		
	2/3:2010		
UK Protection	Over Voltage, Short Circuit,		
OK Protection	Thermal		
Part B Fire Rating	Solid Timber 30/60/90min, I-		
ruit brile kutilig	Joist 30min		
Power Factor	0.90		

PHOTOMETRICS @ 25°C

Pro	duct code	Finish	Туре	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
DL	282WHNWDIM	Matt white	Standard	6W	4000K	38°	650	108	1391	A D
DL2 M	282WHWWDI	Matt white	Standard	6W	3000K	38°	600	100	1284	A D

WIRING INFORMATION

Cable / Flying Lead	0.15m (Class II, complete with Easy-Fit connector)
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel
Input Cable Type	H03VVH2-F (2 CORE 0.75MM)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	Yes (mains)	1 (Ceiling only)	N/A	N/A

ACCESSORIES

DM298FP	Faceplate dimmer	Sold Separately
DM298GRID	Grid dimmer	Sold Separately



LIGHTING INNOVATION



Quick and easy installation with easy-fit connector



High efficacy of 108lm/W



Insulation coverable

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Only 6W

Mains dimmable

Plaster-in downliak

Recessed fitting for lower glare ratin

Flexible driver position for easy installation

Emeraency version available

When using a converter plate, the IP rating is not affected; however, the product is no longe fire-rated.

PATENT: **GB2487912 GB2512715**

