



GENBAY

Ultra-slim and lightweight highbay for lighting general applications

FEATURES

| IP rating | IP65 |
|-------------------------|------------------------------|
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| S O-+i | On-Off Microwave sensor & |
| Sensor Option | daylight switching available |
| Dimmable Option | No |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM6 |
| Emergency Option | Yes, using converter |
| | |

INSTALLATION INFORMATION

| Input | 220-240V AC |
|-----------------------------|-------------------------|
| Maximum Ambient Temperature | -30°C - 40°C |
| Weight | 0.82kg - 1.12kg - 1.5kg |
| Inrush Current | 10A 100us |
| Construction Material | Aluminium ADC12, |
| Construction Material | Polycarbonate Diffuser |
| SELV | No |
| Electric Class (1, 2, 3) | 1 |
| Install Connector Type | Flying lead |
| UK Building Regulations | Part P & L |
| Mounting Options | Jack Chain or Rod Mount |
| Power Factor | 0.984 |

PHOTOMETRICS @ 25°C

| Product code | Finish | Туре | w | Colour | Beam | lm | lm/W | Energy |
|--------------|--------|--------|------|--------|------|-------|------|-------------|
| HBG1N40 | Grey | On-Off | 100W | 4000K | 110° | 13500 | 135 | A G E |
| HBG2N40 | Grey | On-Off | 150W | 4000K | 110° | 19500 | 130 | A E |
| HBG3N40 | Grey | On-Off | 200W | 4000K | 110° | 26000 | 130 | A G E |

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| Cable / Flying Lead | Pre-wired with 1.0m H05RN-F 3x1.0mm ² Ø7mm |
|-------------------------|---|
| Type of Wiring Required | Parallel |
| Series / Parallel | Parallel |

ACCESSORIES

| HBGMWS | Microwave sensor kit inc junction box and counterweight | Sold Separately |
|-----------|---|-----------------|
| HBGEMC1MS | Manual & Self-Test Switchable Emergency Converter | Sold Separately |



LIGHTING INNOVATION



High efficacy of 135lm/W



Sensor kit includes junction box and counter weight



Manual/Self-Test Emergency

WARRANTY

Warranty 3 year
Battery Warranty 3 year
On-Site Warranty 2 year

FEATURES & BENEFITS

Economical high bay for fast return or investment

Easy to add microwave sensor kit includes junction box and counter weight

On/off control with time delay and daylight switching (8-15 metres max)

Ultra slim and light weight highbay for easy handling

Pre-wired with 1.0m H05RN-F 3x1.0mm² Ø7mm

catenary wire suspension

IK08 for robust impact protection

IP65 both luminaire and emergency pack



